

EXTRAORDINARY PUBLISHED BY AUTHORITY

No.1831, CUTTACK, THURSDAY, SEPTEMBER 26, 2024/ASWINA 4, 1946

HOUSING & URBAN DEVELOPMENT DEPARTMENT

NOTIFICATION

The 26th September, 2024

No.19469—HUD-REFM-MISC-0011/2024/HUD.— Government in Housing & Urban Development Department is implementing 24X7 water supply systems with Drink From Tap (DFT) quality water in many Urban Local Bodies (ULBs) in the State. Since provisions of DFT quality supply is stated to be scaled up to all ULBs in a phased manner , it is now felt necessary for notifying a water quality monitoring protocol to be followed by the WATCO and PHEO which would have specific parameters to be tested and the periodicity of the testing while providing the drinking water to the inhabitants of ULBs.

- 2. Whereas, the Bureau of Indian Standards (BIS) vide IS 10500:2012 and its subsequent amendments prescribes the testing parameters for assessing water quality, standards that must be met for making the water potable and prescribes the method of sampling and test for drinking water.
- **3.** And, Whereas, the Central Public Health and Environment Engineering Organisation (CPHEEO) Manual provides comprehensive guidelines for management of 24X7 Pressured Water Supply System (24X7 PWSS) with drink from tap meeting drinking water quality standard IS. 10500:2012.
- **4.** And, whereas, Government of Odisha vide Notification No. 5860/HUD., Dated the 11th March, 2024 had constituted a Technical Advisory Committee (TAC) for recommending drinking water quality standards to be followed and protocol for testing of samples for drinking water in all Urban Local Bodies of the State.
- 5. The Technical Advisory Committee has submitted its report recommending the water quality parameters to be tested at source of water

(both ground and surface), water treatment plants, distribution systems, sources other than piped water supply and during water related incidences along with periodicity of the tests and the laboratory which will carry out the tests for ensuring supply of safe drinking water in all urban local bodies of the State.

- 6. After careful consideration, the Government in Housing & Urban Development Department is pleased to notify that the drinking water supply in the ULBs of the State shall comply with the location specific parameters to be tested and the periodicity of the testing as per Tables 1-10 Schedule attached as **ANNEXURE-1** with the notification.
- **7.** It shall come into force on such date as the State Government may notify separately.

By Order of the Governor

USHA PADHEE

Principal Secretary to Government

SCHEDULE FOR LOCATION SPECIFIC PARAMETERS TO BE TESTED AND THE PERIODICITY OF THE TESTING FOR IS: 10500 DRINKING WATER STANDARD

TABLE -1: TESTING OF SAMPLES AT SOURCE OF DRINKING WATER : RIVERS;			
LAKES: RESERVOIRS			
Parameters to be tested		Test to be carried	Periodicity of Test
		out by	
Physical Parameters	Colour, Odour,	Regional Laboratory	Four times/ year i.e.,
(6)	Temperature , pH.	Total 25 Parameters	January-March
	Turbidity, Total		(Lean Flow)
	Dissolved Solid		April-June (Pre
	(TDS).		monsoon)
General Parameters	Dissolved Oxygen,		July- September
(17)	Total Alkalinity.		(Monsoon)
	Total		October-
	Hardness,Ammonia,		December (Post
	Iron, Nitrate (NO3),		Monsoon)
	Fluoride , Chloride,		
	Phosphate (PO4),		
	Bio-Chemical		
	Oxygen Demand		
	(BOD), Chemical		
	Oxygen Demand		
	(COD), Sodium,		
	Potassium,		
	Manganese,		
	Calcium,		
	Magnesium,		
	Sulphate		
Bacteriological	Fecal Coliform		
Parameters (2)	Total Coliform		

General Parameters	Aluminium, Anionic	Zonal Laboratory	Two times/ year i.e.,
(11)	detergent , Barium,	Total 43	April-June (pre)
	Boron, Copper,	Parameters	monsoon)
	Mineral,Oil, Phenolic		July-September
	Compound, Selenium,		(Monsoon)
	Silver, Sulphide, Zinc		
Bacteriological	Thermotolerant		
Paramaters (1)	Bacteria		
Toxic Parameter (11)	Cd, CN, Pb, Hg,		
	Molybednum (Mo), Ni,		
	Polychlorinated		
	Biphenyl,		
	Poly Aromatic		
	Hydrocarbons (PAH),		
	Total Arsenic, Total		
	Chromium, Uranium		
Radioactive	Alpha Emitter		
Parameter (2)	Beta Emitter		
Pesticide	Alachlor, Atrazine,		
Residue(18)	Aldrin/ Diedrin, Alpha		
	HCH, Beta HCH, Butachlor,		
	Chlorpyriphos.		
	Delta HCH.2,4-		
	dichlorophenoxyasetic acid. DDT (a.p and		
	p.p-Isomers of		
	DDT,DDE and DDD),		
	Endosulfan (alpha,		
	beta and sulphate),		
	Ethion, Gamma HCH(Lindane),		
	Isoprotiron, Malathion,		
	Methyl Parathion,		
	Monocrotophos, Phorate		
Location specific			
parameters	Health Dept. And any		
Paramotoro	other Govt. Dept.		

Note:

- 1. In case any abnormality is observed, frequency of monitoring may be increased from quarterly to either monthly or fortnightly, to get a better trend of the contaminating parameter and to identify the source of contamination.
- 2. In case of lean flow rivers, the above testing is to be carried out once in every two months until there is flow in the river.
- In case the Regional Laboratory is not able to carry out the 25 parameter due to any reasons the same can be carried out either by the Zonal Laboratory & State Laboratory.

TABLE-2: TESTING OF SAMPLES AT SOURCE OF WATER: GROUNDWATER (PRODUCTION WELL/ BOREWELL/ TUBE WELL/ DUG WELL/ SHALLOW WELL)

(One time for Baseline Data)

Parameters to be tested

Test to be carried by

Periodicity of Test

All relevant parameters as Zonal Laboratory

Baseline Data for existing source and while selecting a new source

TABLE-3: TESTING OF SAMPLES AT SOURCE OF WATER: GROUNDWATER			
(PRODUCTION WELL/ BOREWELL/ TUBE WELL/ DUG WELL/ SHALLOW WELL)			
Parameters to be test	ted	Test to be carried out by	Periodicity of Test
Physical	Colour , Odour, pH,	Regional Lab	Two times/ year
Parameters (5)	Turbidity, Total	(Total 21 Paramaters)	i.e.,
	Dissolved Solid		April-June
	(TDS)		(pre monsoon)
General Parameters	Total Alkalinity, Total		October-
(14)	Hardness, Ammonia,		December
	Iron, Nitrate (NO3),		(Post Monsoon)
	Fluoride, Chloride,		,
	Phosphate (PO4),		
	Chemical Oxygen		
	Demand (cod),		
	Sodium, Potassium,		
	Calcium, Magnesium,		
	Sulphate		
Bacteriological	Fecal Coliform		
Parameters (2)	Total Coliform		

General Parameters	Copper, Phenolic	Zonal Lanouatory	Two times/ year
(6)*	Compound, Selenium,		i.e.,
	Silver, Sulphide, Zinc		April-June (pre
Bacteriological	Thermotolerant	(Total 31 Parameters)	monsoon)
Parameters (1)	Bacteria		October-
Toxic Parameters (6)*	Cd. Hg. Ni. Arsenic,		December
	Lead, Total		(Post
	Chromium/		Monsoon)
	Hexavalent chromium		
Pesticide Residue	Alachlor, Atrazine		
(18)*	Aldrin/ Dieldrin, Alpha		
	HCH, Beta HCH,		
	Butachlor,		
	Chlorpyriphos, Delta		
	HXH, 2.4-		
	dichlorophenoxyasetic		
	acid, DDT (a.p		
	andp.p-Isomers of		
	DDT, DDE and		
	DDD), Endosulfan		
	(alpha, beta and		
	sulphate), Ethion,		
	Gamma-HCH		
	(Lindane),		
	Isoproturon,		
	Malathion, Methyl		
	Parathion,		
	Monocrotophos,		
	Phorate		
Other location	As recommended by		
specific Parameters	Health Dept. And any		
	other Govt. Dept.		
	Particularly fluorosis		

affected districts	
Nuapada, Nayagarh,	
Angul with respect to	
Fluoride and chronic	
kidney disease	
affected districts	
Dhenkanal, Cuttack,	
Sambalpur, Baragarh,	
Sundargarh, with	
respect to heavy	
mental likes	
Cadmium, Mercury,	
Lead.	
Leau.	

^{*}These Parameters are site specific, should be monitored based on Baseline data as per Table 2

TABLE-4:ONLINE MONITORING OF WATER			
AT INLET AND OUTLET OF WATER TREATMENT PLANT			
Parameters to be tested Test to be carried out at			
Colour, pH, Turbidity (NTU), Electrical At the inlet raw water channel and at outlet			
conductivity (EC)/Total Dissolved Solids of clarifloculator, at outlet of filter beds an			
(TDS), Freee Residual chlorine(only at at outlet of clear water pump house in the			
outlet) (5 parameters)	WTP through sensors		

TABLE- 5: WATER TREATMENT PLANT			
Parameters to be		Test to be carried	Periodicity of Test
tested		out by	
Physical	Inlet: pH, Turbidity,	WTP laboratory at	Daily
Parameters(6)	Total Alkalinity	inlet and outlet	
	Outlet :Colour,	(Total 8 Parameters)	
	Odour, Electrical		
	Conductivity / Total		
	Dissolved Solids		
	(TDS)		

General Parameter	Free Residual
(1)	Chlorine (only at
	outlet)
Bacteriological	Total Coliform/ Fecal
Parameter (1)	Coliform
Other Test	Jar test for pH. Total
	Alkalinity and
	Turbidity (Only at
	Inlet)

General Parameter (7)	Chloride (as Cl), Nitrate (as NO ₃), Sulphate (as SO ₄) Chemical Oxygen Demand (COD) Ammonia (as Total Ammonia-N) Iron (as Fe) Aluminium (as Al)	Regional Laboratory (Total 09 paramaters)	Once in a month
Bacteriological Parameters (1)	Faecal Coliforms (FC)		
Other Parameter (1)	Langelier Index (once in a year)Temperature, pH, TDS, Calcium,Total Alkalinity		
General Parameters (2)	Chloramine, TOC	Zonal Laboratory Total 06 parameters	Two times/ year i.e.,
Toxic Parameter (4)	Trihalomethane, (Bromoform, Dibromocholoromethane, Bromodicholoromethane, Chloroform		 April-June (pre monsoon) July- September (Monsoon)

TABLE-6: ONLINE MONITORING OF WATER AT ESR/UGR/OGR LEVEL			
Parameters to be	Test to be carried out at	Remarks	
tested			
Colour, pH, Turbidity	ESR/UGR/OGR inlet and outlet	In the event of failure or	
(NTU), Electrical	through sensors	absence of online monitoring	
Conductivity (EC) /		system, the WTP Lab shall	
Total Dissolved Solids		conduct these tests.	

(TDS), Free Residual	
Chlorine	
(5 Parameters)	

TABLE-7: WATER DISTRIBUTION SYSTEM			
Parameters to be tested		Test to be	Periodicity of Test
		carried out by	
General Parameter (08)	pH, Total Dissolved	Regional	Every day randomly
	Solids (TDS),	Laboratory	selected 5-10 samples
	Turbidity (NTU),	(Total 09	for each region with
	Free Residual	parameters)	priority to
	Chorine, Chemical		contamination hot-
	Oxygen Demand,		spots*.
	Nitrate (as NO ₃),		
	Sulphate (as SO ₄),		
	Ammonia (as Total		
	Ammonia-N)		
Bacteriological	Faecal Coliform		
Parameters (01)	(FC)	41	was at its side at at water

*Contamination hot-spots means place where there is recurrent incident of water contaminations in the distribution system such as slums overcrowded areas and areas with pipes laid along drains

TABLE-8: TESTING BY JAL SYSTEM						
Parameters to be tested	Periodicity of Test					
Free Residual Chlorine, H ₂ S strip	100 pair of samples per month as per					
(2 parameters)	H&UD. Notification No.6006/HUD, dated					
	the 12th March, 2024 (copy enclosed					
	Annexure-IV)					
pH, Turbidity, (NTU), Electrical Conductivity	Each Jal Sathi will test water sample for					
(EC) / Total Dissolved Solids (TDS).	three parameters at least once a week					
(3 Parameters)						

TABLE-9: OTHER THAN PIPED WATER SUPPLY					
Parameter	rs to be tested	d	Test to be carried	Periodicity of Test	
			out by		
General	Parameter	pH, Total Dissolved	Regional	Every month	
(07)		Solids (TDS),	Laboratory (Total 8		

	Turbidity (NTU), Nitrate (as NO3), Ammonia (as Total Ammonia-N). Fluoride (as F) Iron (as Fe)	parameters)	randomly selected 5-10 samples per operational zone to be done
Bacteriological	Faecal Coliform (FC)		by Site
Parameters (01)			Engineer.
			 During flood or
			any natural
			calamity
			immediate
			monitoring is to
			be done by Site
			Engineer at
			public and
			private sources

TABLE-10: TESTING DURING WATER RELATED INCIDENT					
Parameters to be tested		Test to be carried out by	Periodicity of Test		
General Param (04)	ter pH, Total Dissolved Solids (TDS), Turbidity (NTU), Free Residual Chorine.	Regional Laboratory (Total 6 parameters)	During water related incident monitoring to be carried out by Site Engineer at		
Bacteriological Parameters (02)	Total Coliform (TC) Faecal Coliform (FC)		public and private sources		